1 2

37

10A NCAC 15 .0804 is amended with changes as published in NCR 29:21, pp. 2437-2445, as follows:

4			
3	10A NCAC 15.	.0804	AREA REQUIREMENTS
4	(a) The local components of an analytical x ray system RGDs shall be so located located and arranged and shall		
5	include to include sufficient shielding or access control that to ensure no radiation levels exist in any area surrounding		
6	the local component group which components that could result in a dose to an individual present therein in excess of		
7	the dose limits given in Rule .1611 .1611(a) of this Chapter. For systems utilizing x ray tubes, these levels shall be		
8	met at any specified tube rating. A registrant or licensee may apply to the agency for an exemption from this		
9	requirement pursuant to Rule .0106(a) of this Chapter.		
10	(b) Surveys Survey Requirements		
11	(1)	Radiation surveys, as required by Rule .1613 as set forth in Rule .1613(a) and (b) of this Chapter,	
12		of all ar	halytical x-ray systems <u>RGDs</u> sufficient to show compliance with Paragraph (a) of this Rule,
13		shall be	performed:
14		(A)	upon installation of the equipment; within 30 days after initial operation of the device;
15		(B)	prior to use following any change in the initial [arrangement,] [arrangement] including the
16			number or type of local components in the system; and
17		(C)	prior to use following any maintenance requiring the disassembly or removal of a local
18			component in the system which that could affect the radiation exposure to personnel;
19			personnel.
20		(D)	radiation monitoring shall be performed during maintenance.
21	(2)	A licens	see or \underline{A} registrant may apply to the agency for approval of procedures differing from those
22		in Subp	aragraph (b)(1) of this Rule, provided that the licensee or registrant demonstrates satisfactory
23		complia	nce with Paragraph (a) of this Rule.
24	(3)	Surveys	[must] shall be performed with a radiation survey instrument capable of the following:
25		<u>(A)</u>	measuring the radiation energies of the system surveyed;
26		<u>(B)</u>	confirming that the radiation limits of this Section are met; and
27		<u>(C)</u>	calibrated according to the manufacture's recommended frequency or at least annually
28			when a frequency is not recommended.
29	(c) Each area of use or room containing analytical x ray equipment <u>RGDs</u> shall be conspicuously posted with a sign		
30	or signs caution signs in accordance with the requirements of Rule .1623 of this Chapter, bearing the radiation caution		
31	symbol and the words "CAUTION - X-RAY EQUIPMENT", EQUIPMENT," or words having a similar intent.		
32	meaning.		
33			
34	History Note:		ty G.S. 104E-7; <u>104E-7(a)(2);</u>
35		Eff. Feb	oruary 1, 1980;
36		Amende	ed Eff. January 1, 1994;

Transferred and Recodified from 15A NCAC 11 .0804 Eff. February 1, 2015. <u>2015;</u>

Amended Eff. October 1, 2015.