- 1 10A NCAC 13E .0312 is proposed for adoption as follows:
- 2

3 10A NCAC 13E .0312 OUTSIDE ENTRANCE AND EXITS

- 4 (a) Each overnight respite services program shall have at least two exit doors on all floor levels. If there are only two
- 5 exit doors, the exit or exit access door shall be located and constructed to minimize the possibility that both may be
- 6 <u>blocked by a fire or other emergency condition.</u>
- 7 (b) One exterior door shall have a minimum width of three feet. Another exterior door shall have a minimum width
- 8 of two feet and eight inches. For the purposes of this Rule, an "exterior door" means a door used by a participant to
- 9 enter the building from the outdoors and to exit the building to the outdoors.
- 10 (c) At least one principal exterior door for the participants' use shall be at grade level or accessible by a ramp with a
- 11 <u>one inch rise for each 12 inches of ramp length</u>. For the purposes of this Rule, a "principal exterior door" means a
- 12 door that is used by participants to access the vehicular pick-up and drop-off area. If the overnight respite services
- 13 program serves any participant who must have physical assistance with evacuation, the building shall have two exterior
- 14 doors at grade level or accessible by a ramp.
- 15 (d) All exit door locks shall be easily operable, by a single hand motion, from the inside at all times without keys.
- 16 Deadbolts or turn buttons on the inside of exit doors shall be disabled.
- 17 (e) Exit doors shall be free of all obstructions or impediments to allow for full instant use in case of fire or other
- 18 <u>emergency.</u>
- 19 (f) All steps, porches, stoops, and ramps shall be provided with handrails or guardrails.
- 20 (g) In each overnight respite services program with at least one participant who is determined by a physician or is
- 21 otherwise known to be disoriented or who wanders, each exit door for participant-use shall be equipped with a
- 22 sounding device that is activated when the door is opened. The sound shall be of sufficient volume that it can be heard
- 23 by staff. If a central system of remote sounding devices is provided, the control panel for the system shall be located
- 24 in the office area or in a location accessible only to staff authorized by the administrator to operate the control panel.
- 25
- 26 History Note: Authority G.S. 131D-6.1;
- 27 <u>Eff. April 1, 2017.</u>