

1 10A NCAC 14J .1213 is proposed for readoption with substantive changes as follows:

2  
3 **10A NCAC 14J .1213 SHOWERS AND PLUMBING FIXTURES**

4 (a) Each jail shall provide at least one shower for every eight inmates.

5 (b) ~~Showers~~ A shower stall floor shall have drains be sloped to a floor drain that prevent prevents water from draining  
6 outside the ~~shower, and the shower fixtures and drains shall be tamper resistant if necessary for security.~~ shower stall.  
7 The floor used to access the shower stall that is outside of the stall but contiguous to the shower stall floor shall be  
8 sloped to a floor drain.

9 (c) In inmate accessible areas, the shower fixture and floor drain cover shall be security-type and tamper-resistant as  
10 rated by the manufacturer.

11 ~~(d) Plumbing~~ In inmate accessible areas, plumbing fixtures shall be made of stainless steel or other materials as  
12 necessary for security. similar materials that are rated as security-type and tamper-resistant by the manufacturer.

13 ~~(d) Drinking fountains shall be equipped with mouth guards.~~

14 (e) All privacy partitions in showers and bathrooms shall be high enough to allow limited privacy for the inmates  
15 while still allowing ~~adequate~~ supervision of the inmates by officers.

16  
17 *History Note: Authority G.S. 153A-221;*

18 *Eff. June 1, 1990-1990;*

19 *Readopted Eff. December 1, 2018.*