1 10A NCAC 13K .1209 is proposed for amendment as follows:

2

## 10A NCAC 13K .1209 HOSPICE INPATIENT REQUIREMENTS FOR GENERAL ELECTRICAL

- 4 (a) All main water supply shut off valves in the sprinkler system must be electronically supervised so that if any valve
- 5 is closed an alarm will sound at a continuously manned central station.
- 6 (b) No two adjacent emergency <u>life safety branch</u> lighting fixtures shall be on the same circuit.
- 7 (c) Receptacles in bathrooms must have ground fault protection.
- 8 (d) Each patient bed location must be provided with a minimum of four eight single or two four duplex receptacles.
- 9 (e) Each patient bed location must be supplied by at least two branch circuits. circuits, one from the equipment branch
- and one from the normal system.
- 11 (f) The fire alarm system must be installed to transmit an alarm automatically to the fire department that is, legally
- 12 committed to serve the area in which the facility is located, by the direct and reliable method approved by local
- 13 ordinances.
- 14 (g) In patient areas, fire alarms shall be gongs or chimes rather than horns or bells.

15

- 16 History Note: Authority G.S. 131E-202;
- 17 Eff. June 1, 1991;
- 18 Pursuant to G.S. 150B-21.3A, rule is necessary without substantive public interest Eff. December
- 19 22, <del>2018.</del> <u>2018:</u>
- 20 Amended Eff. October 1, 2021.